



Zest-it® and the Logo are registered Trade Marks.

Safety Data Sheet Zest-it® Glazing Medium

According to EC directive 91/155/EEC and subsequent amendments

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Product Name	Zest-it® Glazing Medium
Product Numbers	ZGML; 50, 125, 250, 500 ZGMH; 50, 125, 250, 500
Application	Glazing Medium for Oil painting.
Supplier	J and T Blackman Ltd. Foxholes Road, Leicester. LE3 1TH Tel: 0844 8005937. Mob. 07885103576 email: msdssupport@zest-it.biz
Container size	125 ml to 1 Litre

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	Einecs No.	Cas-No.	Content	Health (class)	Risk (class)
Aliphatic Hydrocarbon	265-149-8	64742-47-8	40 - 60%	Xn	R65. R66.
Orange Terpenes	232-433-8	8028-48-6	5 - 10%	Xn	R65. R10.
Gum Damar		9000-16-2	10 - 30%	Not classified	
Linseed Oil		8001-26-1	10 - 30%	Not classified	

The Full Text for all R-Phrases are displayed in Section 16

3 HAZARDS IDENTIFICATION

This product is classified as harmful under CHIP(3) Reg.
Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. This product is not expected to be hazardous to the environment.

4 FIRST AID MEASURES

GENERAL INFORMATION	In all cases of doubt or when symptoms persist, seek medical attention. NEVER give anything by mouth to an unconscious person.
INHALATION	If fluid is aspirated into the lungs. Get medical attention immediately. Remove person to fresh air. Keep warm and at rest.
INGESTION	DO NOT induce vomiting. If vomiting occurs, keep head low so the stomach content doesn't get into the lungs. Drink plenty of water or milk. Seek medical attention immediately. Provide rest, warmth and fresh air.

Zest-it® Glazing Medium

According to EC directive 91/155/EEC and subsequent amendments

SKIN CONTACT	Remove any soaked or contaminated clothing and shoes. Wash the skin immediately with soap and water. Do not allow saturated clothing to remain in contact with skin for prolonged periods.
EYE CONTACT	Remove any contact lenses before rinsing. Promptly flush eyes with plenty of water while lifting the eyelids. Continue to rinse for up to 15 minutes. If irritation occurs seek medical attention.

5 FIRE FIGHTING MEASURES

GENERAL INFORMATION	Insoluble in water. Crumpled rags or cloth may spontaneously combust. Dry flat or immerse in water.
EXTINGUISHING MEDIA	Extinguish with foam, carbon dioxide (CO ²), dry powder, soil or water fog. DO NOT use water jet as this will spread the fire.
SPECIAL FIRE FIGHTING PROCEDURES	Suitable self contained breathing apparatus should be used in confined areas. Keep run-off water from fire fighting out of sewers and water courses.
UNUSUAL FIRE & EXPLOSION HAZARDS	May produce dense black smoke. Stay up wind of fire. Vapours are heavier than air and may travel along the ground to nearby sources of ignition. Linseed oil will burn in fierce heat and generate its own heat, care must be taken.
SPECIFIC HAZARDS	Burning product will liberate carbon dioxide (CO ²) and possibly carbon monoxide (CO). Avoid breathing the smoke.

6 ACCIDENTAL RELEASE MEASURES

GENERAL INFORMATION	Spillage can be a slippage hazard. Ventilate well. Extinguish all sources of ignition. Avoid contact with eyes and skin. Do not allow to enter sewers or water courses. Crumpled rags or cloths may spontaneously combust.
SMALL RELEASE CLEAN UP METHODS	Contain and absorb with dry sand, soil or oil absorbent avoiding the use of sawdust. Dispose of as dry oil waste.
LARGE RELEASE CLEAN UP METHODS	Dike with dry sand, soil or other suitable material, avoiding the use of sawdust. Used or contaminated product should not be allowed to enter sewers or water courses.

7 HANDLING AND STORAGE

GENERAL INFORMATION	Avoid prolonged skin contact. Wash after using.
HANDLING	Do not handle or use near open flames or sources of ignition. Do not leave on crumpled rags/cloths possibility of spontaneous combustion, dry flat or wash cloths after use.
STORAGE	Store in closed container in a cool well ventilated place away from sources of ignition. Keep away from sparks, heat and open flames.

Zest-it® Glazing Medium

According to EC directive 91/155/EEC and subsequent amendments

8 EXPOSURE AND PERSONAL PROTECTION

Ingredient (WEL)	LT Exp.(8 hours)	ST Exp. (10 minutes)
Aliphatic Hydrocarbon	1200 mg/m ³	
Orange Terpenes	800 mg/m ³	
Linseed Stand Oil	No exposure limit noted.	
ENGINEERING	No specific ventilation required. Ensure that any plant used in conjunction with this product runs within the product's working temperature range.	
VENTILATION	Adequate natural ventilation will suffice in most instances.	
RESPIRATORY	None required in normal use. Avoid generating mists.	
EYE PROTECTION	None required in normal use. Wear safety glasses where splashing is probable.	
SKIN PROTECTION	None required in normal use. Nitrile gloves are recommended for prolonged use or sensitive individuals.	
HYGIENE	Wash hands after use. Wash contaminated clothing before reuse.	

9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT	180-239°C (356-462°F)
DENSITY (SG)	0.86 - 91 g/cm ³
VAPOUR DENSITY	4.5 @ 80°C (Air=1)
VISCOSITY	Slightly viscous
SOLUBILITY IN WATER	Insoluble
FLASH POINT	over 70°C (152°F) (PMCC)
AUTO IGNITION TEMPERATURE	180°C (356°F) (ASTM E659)
EXPLOSION LIMITS	LeI - 0.6% @ 28°C (82°F) UeI - 6.5% @ 28°C (82°F)
APPEARANCE	Slightly viscous light straw coloured liquid
ODOUR	Citrus Linseed
COLOUR	Straw/yellow liquid

Zest-it® Glazing Medium

According to EC directive 91/155/EEC and subsequent amendments

10 STABILITY AND REACTIVITY

STABILITY	Stabile.
CONDITIONS TO AVOID	Open flames and other sources of ignition. Crumpled rags may self combust. Dry flat or immerse in water.
INCOMPATIBILITY	Avoid contact with strong oxidizing agents and acids.
HAZARDOUS DECOMPOSITION	None expected under normal circumstances. By combustion: as with any organic material, combustion will liberate Carbon Dioxide (CO ²) and possibly Carbon Monoxide (CO).
HAZARDOUS POLYMERIZATION	Does not occur

11 TOXICOLOGICAL INFORMATION

ROUTE OF ENTRY	Skin and/or eye contact.
INGESTION	Small amounts of vomited liquid ingested or aspirated into lungs may cause bronchopneumonia.
INHALATION	Not relevant at normal room temperatures. When heated irritating vapours may be formed.
EYE	Splashes may irritate.
SKIN	Acts as a defatting agent on skin. Prolonged skin contact may aggravate dermatitis in sensitive individuals and cause skin dryness or cracking.
HEALTH WARNINGS	This product has low toxicity. Only large volumes may have adverse impact on human health. This substance has no evidence of carcinogenic properties.

12 ECOLOGICAL INFORMATION

ECOLOGICAL HAZARD	None expected.
BIODEGRADATION (EEC)	Biodegradable. Liquid will evaporate readily.
DEGRADATION	Inherently biodegradable (OECD). No acute toxicity to aquatic organisms is expected.
BIOACCUMULATION	Should not occur.

13 DISPOSAL CONSIDERATIONS

DISPOSAL	Used or contaminated product should be disposed of in accordance with the contaminate. Waste to be treated as controlled waste. Disposal to licensed waster disposal site in accordance with local Waste Disposal Authority or appropriate local body.
----------	--


Zest-it® Glazing Medium

According to EC directive 91/155/EEC and subsequent amendments

14 TRANSPORTATION INFORMATION

GENERAL INFORMATION	This product is not regulated for transport and is not a marine pollutant. Intrastate Ref. 2910-10-90
DOT LABELING	Not applicable.
HAZARD CLASS	Not applicable.

15 REGULATORY INFORMATION

LABELLING	 Harmful
LABEL RISK PHRASES	R-65 Harmful: may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking.
LABEL SAFETY PHRASES	S-62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label. S-37 Wear suitable gloves
CONTAINS	Aliphatic Hydrocarbon: Citrus Oil: Linseed Oil: Gum Damar:
UK REGULATORY REFERENCE	Chemicals (Hazard Information & Packaging for Supply) (CHIPS 3)
APPROVED CODE OF PRACTICE COSHH	Classification and Labelling of Substances and Preparations Dangerous for Supply.

16 OTHER INFORMATION

DATE	01/Jul/2008
SHEET REF. No.	Zest-it Glazing Medium
PRODUCT COVERED BY THE SHEET	All sizes of Zest-it Glazing Medium Light and Heavy
RISK PHRASES IN FULL	R-10 Flammable R-65 Harmful, may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking.

Disclaimer. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information contained in this document is furnished without warranty, guarantee or representation of any kind to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own particular use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Copyright © J and T Blackman Ltd. 1996