



Zest-it® and the Logo are registered Trade Marks.

## Zest-it Cold Pressed Linseed Oil

### Safety Data Sheet

For occupational use not general public/consumer use

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING					
Product Name	Zest-it® Cold-Pressed Linseed Oil				
Product Numbers	ZCPLO; 50, 125, 250, 500, 1000				
Application	Medium for Oil pigment and paint.				
Supplier	J and T Blackman Ltd. Store Room, Foxholes Road, Leicester. LE3 1TH Tel: 0844 8005937. Mob. 07885103576 email: msdssupport@zest-it.biz				
Container size	50 ml to 1 Litre				
2 COMPOSITION/INFORMATION ON INGREDIENTS					
Name	Einecs No.	Cas-No.	Content	Health (class)	Risk (class)
Cold Pressed Linseed Oil			90 - 100%	Not classified	
3 HAZARDS IDENTIFICATION					
Not regarded as a health or environmental hazard.					
4 FIRST AID MEASURES					
GENERAL INFORMATION	In all cases of doubt or when symptoms persist, seek medical attention. NEVER give anything by mouth to an unconscious person.				
INGESTION	DO NOT induce vomiting. If vomiting occurs, keep head low so the stomach content doesn't get into the lungs. Drink plenty of water or milk. Seek medical attention.				
SKIN CONTACT	Remove any soaked or contaminated clothing and shoes. Wash the skin with soap and water. Get medical attention if irritation persists.				
EYE CONTACT	Remove any contact lenses before rinsing. Promptly flush eyes with plenty of water while lifting the eyelids. Continue to rinse for up to 15 minutes. Get medical attention if any discomfort continues.				
5 FIRE FIGHTING MEASURES					
GENERAL INFORMATION	Classification: non-flammable. Flash point: 220°C (446°F). Insoluble in water. Crumpled rags or cloth may spontaneously combust. Dry flat or immerse in water.				
EXTINGUISHING MEDIA	Extinguish with foam, carbon dioxide (CO <sup>2</sup> ), dry powder, soil or water fog. DO NOT use water jet as this will spread the fire.				
SPECIAL FIRE FIGHTING PROCEDURES	Suitable self contained breathing apparatus should be used in confined areas. Keep run-off water out of sewers and water courses.				
UNUSUAL FIRE & EXPLOSION HAZARDS	May produce dense black smoke. Stay up wind of fire. Linseed oil will burn in fierce heat and generate its own heat, care must be taken.				
SPECIFIC HAZARDS	Burning product will liberate carbon dioxide (CO <sup>2</sup> ) and possibly carbon monoxide (CO). Avoid breathing the smoke.				
6 ACCIDENTAL RELEASE MEASURES					
GENERAL INFORMATION	Ventilate well. Extinguish all sources of ignition. Avoid contact with eyes and skin. Do not allow to enter sewers or water courses. Crumpled rags or cloths may spontaneously combust.				
SMALL RELEASE CLEAN UP METHODS	Contain and absorb with dry sand, soil or oil absorbent avoiding the use of sawdust. Dispose of as dry oil waste.				
LARGE RELEASE CLEAN UP METHODS	Dike with dry sand, soil or other suitable material, avoiding the use of sawdust. Used or contaminated product should not be allowed to enter sewers or water courses.				
7 HANDLING AND STORAGE					
GENERAL INFORMATION	Avoid spillage/slippy surface. Wash area with soap and water.				
HANDLING	Do not handle or use near open flames or sources of ignition. Do not leave on crumpled rags/cloths possibility of spontaneous combustion, dry flat or wash cloths after use.				
STORAGE	Store in closed container in a cool well ventilated place away from sources of ignition.				

## Zest-it Cold Pressed Linseed Oil

<b>8 EXPOSURE AND PERSONAL PROTECTION</b>	
VENTILATION	Adequate natural ventilation will suffice in most instances.
RESPIRATORY	None required in normal use.
EYE PROTECTION	None required in normal use.
SKIN PROTECTION	None required in normal use.
HYGIENE	Wash hands after use.
<b>9 PHYSICAL AND CHEMICAL PROPERTIES</b>	
BOILING POINT	300 <sup>0</sup> C (572 <sup>0</sup> F)
DENSITY (SG)	0.93 g/cm <sup>3</sup>
VISCOSITY	Slightly viscous
SOLUBILITY IN WATER	Insoluble
FLASH POINT	over 220 <sup>0</sup> C (446 <sup>0</sup> F)
APPEARANCE	Clear amber coloured liquid
ODOUR	Characteristic Linseed smell
<b>10 STABILITY AND REACTIVITY</b>	
STABILITY	Stabile.
CONDITIONS TO AVOID	Open flames and other sources of ignition. Crumpled rags may self combust. Dry flat or immerse in water.
INCOMPATIBILITY	Avoid contact with strong oxidizing agents and acids.
HAZARDOUS DECOMPOSITION	None expected under normal circumstances. By combustion: as with any organic material, combustion will liberate Carbon Dioxide (CO <sup>2</sup> ) and possibly Carbon Monoxide (CO).
HAZARDOUS POLYMERIZATION	Does not occur
<b>11 TOXICOLOGICAL INFORMATION</b>	
ROUTE OF ENTRY	Skin and/or eye contact.
INGESTION	Non-toxic.
INHALATION	Not relevant at normal room temperatures.
EYE	Non-irritant.
SKIN	Non-irritant.
CARCINOGENICITY LISTING	NPT - None. IARC - None. OSHA - None. ACGIH - None.
<b>12 ECOLOGICAL INFORMATION</b>	
ECOLOGICAL HAZARD	None expected.
BIODEGRADATION (EEC)	Biodegradable.
BIOACCUMULATION	Should not occur.
<b>13 DISPOSAL CONSIDERATIONS</b>	
DISPOSAL	Not considered a hazardous waste. This product is classified as Biodegradable. In its purchased state it may be disposed of as oil waste. Used or contaminated product should be disposed of in accordance with the contaminate.
<b>14 TRANSPORTATION INFORMATION</b>	
GENERAL INFORMATION	This product is not regulated for transport and is not a marine pollutant.
DOT LABELING	Not applicable.
HAZARD CLASS	Not applicable.
UN No.	Not applicable.
<b>15 REGULATORY INFORMATION</b>	
CONTAINS	Cold Pressed Linseed Oil
RISK PHRASES	Not Classified
SAFETY PHRASE	Not Classified

## Zest-it Cold Pressed Linseed Oil

UK REGULATORY REFERENCE	Chemicals (Hazard Information & Packaging for Supply) (CHIPS 3)
APPROVED CODE OF PRACTICE COSHH	Classification and Labelling of Substances and Preparations Dangerous for Supply.
<b>16 OTHER INFORMATION</b>	
DATE	01/Oct/2009
SHEET REF. No.	Zest-it Cold-Pressed Linseed Oil
PRODUCT COVERED BY THE SHEET	All sizes of Zest-it Cold-Pressed Linseed Oil
REPLACES SHEET	01/Sep/2009

Disclaimer. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information contained in this document is furnished without warranty, guarantee or representation of any kind to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own particular use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Since the specific conditions of use of the product are outside the control of the supplier, the user is responsible for ensuring that the requirements of safety and relevant legislation are complied with.